



WHEN CONCRETE EXISTS BELOW ASPHALT T-CUT SHALL EXTEND 6" MIN. FROM EDGE OF CONCRETE AND CONCRETE SHALL BE CUT A MIN. OF 6" FROM EDGE OF TRENCH.

NOTES:

- 1) LIMITS OF TRENCH PATCH SHALL BE APPROVED BY CITY ENGINEER PRIOR TO PAVING. LIMITS WILL BE A MINIMUM OF 12" FROM EDGE OF TRENCH.
- 2) AC PAVEMENT SHALL BE REPLACED WITH AC TO A MINIMUM THICKNESS OF 6" OR TO THE THICKNESS OF REMOVED PAVEMENT, WHICHEVER IS GREATER. EACH LIFT SHALL BE A MAXIMUM OF 3". IF PAVING OVER EXISTING CONCRETE, THE ASPHALT PATCH SHALL BE 3" WITH A MINIMUM 6" OFFSET JOINT FROM THE EDGE OF CONCRETE.
- 3) USE 1/2" DENSE LEVEL II WMAC MIX OR AS APPROVED BY CITY ENGINEER. COLD MIX SHALL BE REPLACED WITH 1/2" DENSE LEVEL II WMAC.



**DETAIL FOR
STREET CUT**

DATE: OCTOBER 2023	DRAWING NO. 8
-----------------------	-------------------------